



AquaPlus Package

optical dissolved oxygen • conductivity • TDS
• SSG • resistivity • salinity • temperature

Optical Dissolved oxygen water quality monitoring package

Combined optical dissolved oxygen, conductivity and temperature sensor for portable field use. Package comes complete with 3m cable, GPS meter and carry case

Why Optical?

Traditionally, DO measurement in portable field equipment has been done using membrane covered detectors known as Clark Cells. This type of cell suffers from problems including membrane fouling, calibration instability and worst of all, oxygen consumption. During measurement, a Clark Cell will consume oxygen making it necessary to have a constant flow of water over the cell.

Optical technology eliminates all these problems allowing high precision, membrane-free, long-term stability along with infrequent calibration and immunity to fouling by sulphides and other gases.

The Aquaread AquaPlus is the only Optical DO system that measures salinity directly. This allows for automatic salinity compensation giving you the highest accuracy in any type of water.

The Tech Behind AquaPlus

The Aquaread AquaPlus works on the principle of Dynamic Luminescence Quenching. A gas-permeable material known as a luminophore is excited with short bursts of blue light, which causes molecules in the luminophore to emit red photons. By measuring the delay of the returned red photons with respect to the blue excitation, the level of dissolved oxygen present can be determined.

AquaPlus Mechanical Specification

Protection Class	IP68 (permanent immersion)
Immersion Depth	Min 75mm. Max 100m**
Operating Temperature	-5°C - +70°C
Dimensions (L x Dia)	250mm x 24mm
Weight	400g

**100m submersion for period of 1 week, 30m submersion suitable for permanent deployment.

AquaPlus with the sleeve removed reveals the combined dissolved oxygen, conductivity & temperature sensors. The end cap is replaceable however you can expect more than 2 years life from one cap



AP-2000 / AP-2000-D Aquaprobe Package

pH • ORP • conductivity • TDS • SSG • resistivity • salinity
• optical dissolved oxygen • temperature • depth

Measures more parameters than any other 2" diameter multiparameter probe



Take your portable water quality monitoring to the next level by using the advanced AP-2000 multiparameter probe

AP-2000 / AP-2000-D

The AP-2000 comes pre-loaded with a selection of sensors:

- pH • ORP • conductivity • TDS • SSG • Res • salinity
- optical dissolved oxygen • temperature • depth (AP-2000-D Only)

See back pages for Sensor Specifications

Package comes complete with Aquaprobe, GPS Aquameter, 3m cable, rugged case and accessories. Various cable lengths are available; 10, 20 and 30m as standard.

There are an additional 2 ports allowing you to add more:

Aux port 1 can be fitted with either an optical sensor or an ion selective sensor (ISE)

Aux port 2 can be fitted with only an ISE sensor



ISE Electrode Options:

Ammonium / Ammonia,
Chloride,
Nitrate,
Fluoride,
Calcium.

Optical Electrode Options:

Turbidity,
Chlorophyll,
Blue Green Algae,
Rhodamine,
Fluorescein,
Refined Oil,
CDOM / FDOM.

Aquaprobe Facts

- The IP68 rated Aquaprobe is constructed of marine grade aluminium and is designed for use in fresh, marine and waste-water applications.
- Its metal construction and weight reflect the superior build quality of the instrument.



AP-2000 / AP-2000-D Aquaprobe Package

pH • ORP • conductivity • TDS • SSG • resistivity • salinity
• optical dissolved oxygen • temperature • depth

Measures more parameters than any other 2" diameter multiparameter probe

GPS Aquameter

Every Aquaprobe package comes with a GPS Aquameter for live readings, automatic data recording and probe calibration



"Record the location of every data set using the GPS Aquameter."



3m Cable with AquaConn Connectors

The AP-2000 is fitted with our robust AquaConn metal connectors, each package comes with a 3m cable with AquaConn connectors at each end and Kevlar strands running the length of the cable for extra tensile strength

Flowcell available for every Aquaprobe

Every water quality testing probe has its own flowcell allowing you to bring sample water straight to the probe. This is ideal for ground water monitoring and some process applications



Optical Dissolved Oxygen (DO) Sensor

The AP-2000 has a factory installed and fully calibrated optical DO sensor. The sensor requires much less maintenance than the galvanic version, gives more stable readings and requires cap changes only once every 2 years



AP-2000/2000-D Mechanical Specification

Protection Class	IP68 (permanent immersion)
Immersion Depth	Min 75mm. Max 100m *
Operating Temperature	-5 °C - +70 °C
Dimensions (L x Dia)	290mm x 42mm
Weight	700g

*100m submersion for period of 1 week, 30m submersion suitable for permanent deployment, depth measurement displayed up to 60m on Aquameter.

Water Quality Specifications

Standard Parameters

Dissolved Oxygen	Range	0 – 500.0% / 0 – 50.00 mg/L
	Resolution	0.1% / 0.01mg/L
	Accuracy	0 - 200%: ± 1% of reading, 200% - 500%: ± 10%
Depth AP-2000/ AP-5000	Range	± 0 – 60.00 m (60m max displayed depth, max probe immersion 100m)
	Resolution	1cm
	Accuracy	± 0.5% FS
Depth AP-7000	Range	± 0 – 99.99 m
	Resolution	1cm
	Accuracy	± 0.2% FS
Conductivity (EC)	Range	0 – 200 mS/cm (0 - 200,000 µS/cm)
	Resolution	3 Auto-range scales: 0 – 9999 µS/cm, 10.00 – 99.99 mS/cm, 100.0 – 200.0mS/cm
	Accuracy	± 1% of reading
TDS*	Range	0 – 100,000 mg/L (ppm)
	Resolution	2 Auto-range scales: 0 – 9999mg/L, 10.00 – 100.00g/L
	Accuracy	± 1% of reading
Resistivity*	Range	5 Ω • cm – 1 MΩ • cm
	Resolution	2 Auto-range scales: 5 – 9999 Ω • cm, 10.0 – 1000.0 KΩ • cm
	Accuracy	± 1% of reading
Salinity*	Range	0 – 70 PSU / 0 – 70.00 ppt (g/Kg)
	Resolution	0.01 PSU / 0.01 ppt
	Accuracy	± 1% of reading
Seawater Specific Gravity*	Range	0 – 50 ot
	Resolution	0.1 ot
	Accuracy	± 1.0 ot
pH	Range	0 – 14 pH / ± 625mV
	Resolution	0.01 pH / ± 0.1mV
	Accuracy	± 0.1 pH / ± 5mV
ORP	Range	± 2000mV
	Resolution	0.1mV
	Accuracy	± 5mV
Temperature (non freezing)	Range	-5°C – +50°C (23°F – 122°F)
	Resolution	0.01°C / 0.1°F
	Accuracy	± 0.5 °C

* Readings calculated from EC and temperature electrode values

ISE

Ammonium	Range	0 – 9,000mg/L (ppm)
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 – 8,999.9 mg/L
	Accuracy	± 10% of reading or 2ppm (whichever is greater)
Ammonia [†]	Range	0 – 9,000mg/L (ppm)
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 – 8,999.9 mg/L
	Accuracy	± 10% of reading or 2ppm (whichever is greater)
Chloride	Range	0 – 20,000mg/L (ppm)
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 – 19,999.9 mg/L
	Accuracy	± 10% of reading or 2ppm (whichever is greater)
Fluoride	Range	0 – 1,000mg/L (ppm)
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 – 999.9 mg/L
	Accuracy	± 10% of reading or 2ppm (whichever is greater)
Nitrate	Range	0 – 30,000mg/L (ppm)
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 – 29,999.9 mg/L
	Accuracy	± 10% of reading or 2ppm (whichever is greater)
Calcium	Range	0 – 2,000mg/L (ppm)
	Resolution	2 Auto-range scales: 0.00 - 99.99 mg/L, 100.0 – 1,999.9 mg/L
	Accuracy	± 10% of reading or 2ppm (whichever is greater)

[†] Ammonium electrode required. Readings calculated from ammonium, pH and temperature values.

Optical

Turbidity	Range	0 – 3000 NTU
	Resolution	2 Auto-range scales: 0.0 - 99.9 NTU, 100 - 3000 NTU
	Accuracy	± 5% of auto-ranged scale
Chlorophyll	Range	0 – 500.0 µg/L (ppb)
	Resolution	2 Auto-range scales: 0.00 - 99.99 µg/L, 100.0 - 500.0 µg/L
	Repeatability	± 5% of reading
Phycocyanin (freshwater BGA)	Range	0 – 300,000 cells/mL
	Resolution	1 cell/mL
	Repeatability	± 10% of reading
Phycerythrin (marine BGA)	Range	200 cells/mL
	Resolution	1 cell/mL
	Repeatability	± 10% of reading
Rhodamine WT Dye	Range	0 – 500 µg/L (ppb)
	Resolution	2 Auto-range scales: 0.00 - 99.99 µg/L, 100.0 - 500.0 µg/L
	Accuracy	± 5% of reading
Fluorescein Dye	Range	0 – 500 µg/L (ppb)
	Resolution	2 Auto-range scales: 0.00 - 99.99 µg/L, 100.0 - 500.0 µg/L
	Accuracy	± 5% of reading
Refined Oil	Range	0 – 10,000 µg/L (ppb) (Naphthalene)
	Resolution	0.1 µg/L
	Repeatability	± 10% of reading
CDOM / FDOM	Range	0 – 20,000 µg/L (ppb) (Quinine Sulphate)
	Resolution	2 Auto-range scales: 0.0 – 9,999.9 µg/L, 10,000 – 20,000 µg/L
	Repeatability	± 10% of reading

The accuracy figures quoted throughout this document represent the equipment's capability at the calibration points at 25°C. These figures do not take into account errors introduced by variations in the accuracy of calibration solutions and errors beyond the control of the manufacturer that may be introduced by environmental conditions in the field. Accuracy in the field is also dependent upon full calibration and minimal time between calibration and use.

Water Level Specifications

		LEVELINE (Abs & Gauge)	LEVELINE - BARO	LEVELINE- MINI
General	Temperature ranges (non freezing)	Operational: -20-80° C (-4-176° F) Storage: -40-80° C (-40-176° F) Compensated: -20-80° C (-4-176° F)	Operational: -20-80° C (-4-176° F) Storage: -40-80° C (-40-176° F) Compensated: -20-80° C (-4-176° F)	Operational: -20-80° C (-4-176° F) Storage: -40-80° C (-40-176° F) Compensated: -20-80° C (-4-176° F)
	Diameter	22.2mm (0.875 in)	22.2mm (0.875 in)	22.2mm (0.875 in)
	Length	186mm (7.32 in)	186mm (7.32 in)	87mm (3.43 in)
	Weight	150g (5.3oz)	160g (5.6oz)	120g (4.2oz)
	Materials	Titanium body, Delrin nose cone	Stainless Steel body, Delrin nose cone	Stainless Steel body, Delrin nose cone
	Output options	Modbus/RS485, SDI-12, Aquaread proprietary	Modbus/RS485, SDI-12, Aquaread proprietary	Modbus/RS485, SDI-12, Aquaread proprietary
	Battery type & life	3.6V lithium; 10 years or 5M readings	3.6V lithium; 10 years or 5M readings	N/A
	External power	6 - 30 VDC	6 - 30 VDC	6 - 30 VDC

Memory	Size	8.0 MB	2.0 MB	N/A
	Data Records	500,000	150,000	N/A
	Log types	Linear, Event & User-Selectable Schedule with Future Start, Future Stop, Deploy Start and Real Time View	Linear, Event & User-Selectable Schedule with Future Start, Future Stop, Deploy Start and Real Time View	N/A
	Fastest logging rate & Modbus rate	10 per second	1 per minute (logging) 5 per second (Modbus)	10 per second (Modbus Rate)
	Fastest SDI-12 output rate	1 per second	1 per second	1 per second
	Real-time clock	Accurate to 1 second/24-hr period (± 6 minutes/year)	Accurate to 1 second/24-hr period (± 6 minutes/year)	N/A

Pressure Sensor	Type / Material	Piezoresistive; ceramic		Piezoresistive; ceramic	Piezoresistive; ceramic
	Range (Absolute)	10.0m (32.8 ft) 50.0m (164 ft), 200m (656 ft)	20.0m (65.6 ft) 100m (326 ft)	0 to 16.7 psi; 0 to 1.15 bar	10.0m (32.8 ft) 50.0m (164 ft), 200m (656 ft)
	Range (Gauge)	10.0m (32.8 ft) 50.0m (164 ft), 200m (656 ft)	20.0m (65.6 ft) 100m (326 ft)	N/A	N/A
	Maximum pressure	Max 2x range, Burst 2.5x range		Max 2x range, Burst 2.5x range	Max 2x range, Burst 2.5x range
	Accuracy @ 15° C (See note 1)	±0.05% FS		±0.1% FS	±0.05% FS
	Accuracy (FS) (See note 2)	±0.1% FS		±0.2% FS	±0.1% FS
	Resolution	0.005% FS or 1mm whichever is greater		0.1mb	0.005% FS or 1mm whichever is greater
	Units of measure	Pressure: psi, kPa, bar, mbar, mmHg, inHg, cmH2O, inH2O, Level: in, ft, mm, cm, m		Pressure: psi, kPa, bar, mbar, mmHg, inHg, cmH2O, inH2O.	Pressure: psi, kPa, bar, mbar, mmHg, inHg, cmH2O, inH2O, Level: in, ft, mm, cm, m

Temperature Sensor	Accuracy	±0.1° C	±0.1° C	±0.1° C
	Resolution	0.01° C	0.01° C	0.01° C
	Output Units	Celsius	Celsius	Celsius

Notes: 1) Across factory-calibrated pressure range at a constant temperature. 2) Across factory-calibrated pressure and temperature ranges